



Impression Top

Flat Belts

| | Product | Color | Illustration | Thickness (mm) | Shore hardness | Temperature range | Coefficient of friction |
|--------------------------------|-------------------|-------|-------------------|----------------|----------------|---------------------------------------|-------------------------|
| ITO50 Impression Top Oval | FEMW-ITO-50 | ● | | 2, 2.5, 3 | 95A/46D | -30° C to +60° C | 0.25 |
| | FRMW-ITO-50 | | | 2.5, 3 | | -20° F to +140° F | 0.2 |
| | FHW-ITO-50 | ● | | 2, 2.5, 3 | 59D | -20° C to +75° C -5° F to +170° F | 0.28 |
| | FEMB-ITO-50 | ● | | 2, 2.5, 3 | 95A/46D | -30° C to +60° C | 0.25 |
| | FRMB-ITO-50 | | | 2.5, 3 | | -20° F to +140° F | 0.2 |
| | FELB-ITO-50 | | | 2.5, 3 | 80A | -40° C to +50° C | 0.45 |
| | FRLB-CEBB- ITO-50 | ● | | 2.5 | 80A | -40° to +120° F | 0.35 |
| | FELW-ITO-50 | | | 3 | | -40° C to +50° C | 0.45 |
| FRLW-ITO-50 | 2.5 | | -40° F to +120° F | 0.2 | | | |
| ITR-10 Impression Top Rough | FEL-ITR-10 | ● | | 4 | 80A | -40° C to +50° C -40° F to +120° F | 0.45 |
| | FRL-ITR-10 | ● | | | | | 0.2 |
| | FELW-ITR-10 | ● | | | | | 0.45 |
| | FRLW-ITR-10 | ● | | | | | 0.2 |
| IRT Impression Roof Top | FELB-IRT | ● | | 4 | 80A | -40° C to +50° C -40° F to +120° F | 0.45 |
| | FMB-DD-IRT | | | 3.2 | 95A/46D | -20° C to +60° C | 0.5 |
| | FMB-DDSP -IRT | | | 3.2 | 53A/46D | -5° F to +140° F | |
| | FEMB-IRT | | | 3.5 / 4 | 95A/46D | -30° C to +60° C -20° F to +140° F | 0.25 |
| CT Crescent Top | FELB-CT | ● | | 3 | 80A | -30° C to +60° C | 0.25 |
| | FEMB-CT | | | | 95A/46D | -20° F to +140° F | |
| | FMB-CT | | | | 95A/46D | -30° C to 60° C | 0.40 |
| | FEMW-CT | ● | | 2.5 | 95A/46D | -20° F to 140° F | 0.25 |
| Spikes | FEMB-SP | ● | | 2, 2.5, 3 | 95A | -30° C to +60° C | 0.25 |
| | FEMW-SP | ● | | | | -20° F to +140° F | |
| | FELB-SP | ● | | | 85A | -40° C to +50° C -40° F to +120° F | 0.45 |
| Mini Cleats | FELW-MC | ● | | 2.5, 3 | 80A | -40° C to +50° C -40° F to +120° F | 0.45 |
| | FEMB MC | ● | | 3 | 95A / 46D | -30° C to +60° C | 0.25 |
| | FRMB CB MC | ● | | 3 | 95A / 46D | -20° F to +140° F | 0.45 |

Notes: * All the products are available in standard width of 1524mm/60" except the product FELB-CT which is available in width - 1500mm/59".